

NextGen Dallas/Fort Worth International Airport

Dallas/Fort Worth International Airport (DFW) is the fourth busiest airport in North America in terms of passenger traffic, which grew 5.1 percent in 2014 to reach 63.5 million. The number of operations increased 0.3 percent in 2014 to 679,820. In 2014, DFW was the 11th busiest airport in North America in terms of cargo volume — 39th in the world — with 634,997 metric tons of cargo passing through its facilities. American Airlines' hub in Dallas/Fort Worth serves as the world's second largest airline hub.

Several NextGen capabilities and enabling improvements have been implemented including Airport Surface Detection Equipment-Model X, External Surface Data Release, Adapted for Adjacent Center Metering, Performance Based Navigation procedures, Optimized Profile Descents, basic rerouting, and Adapted for Time Based Flow Management use.

All airport information shown above is reported by Calendar Year (CY).

Scorecard

The following metrics summarize performance over a large set of diverse operations at this location. As such, their purpose is to reflect general trends as experienced by aircraft operators and passengers, without regard to their underlying drivers. For this reason, metric values should not be compared to operational impacts attributed to specific NextGen capabilities, where these are provided.

Reportable Hours for DFW
07:00 - 21:59 local time

All Information below is in Fiscal Years (October 1 - September 30).

- [Efficiency](#)
- [Capacity](#)

Efficiency Performance Indicators

Performance Indicator (FY)	2009	2010	2011	2012	2013	2014	2015	2016
Average Gate Arrival Delay <i>Minutes per Flight</i>								
During reportable hours, the yearly average of the difference between the Actual Gate-In Time and the Scheduled Gate-In Time for flights to the selected airport from any of the ASPM airports. The delay for each fiscal year (FY) is calculated based on the 0.5h — 99.5th	2.8	2.7	-0.7	-0.3	3.5	5.7	6.4	3.5

percentile of the distributions for the year. Flights may depart outside reportable hours, but must arrive during them. The reportable hours vary by airport.								
Average Number of Level-offs per Flight <i>Counts per Flight</i> The count of level-offs as flights descend from cruise altitudes to the arrival airport, averaged for the fiscal year.	1	1	2.1	2.1	2.1	2.1	1.9	1.9
Distance in Level Flight from Top of Descent to Runway Threshold <i>Nautical Miles per Flight</i> The distance flown during level-off segments as flights descend from cruise altitudes to the arrival airport, averaged for the fiscal year (FY).	1	1	28.0	27.8	27.4	27.5	19.2	19.3
Effective Gate-to-Gate Time <i>Minutes per Flight</i> During reportable hours, the difference between the Actual Gate-In Time at the destination (selected) airport and the Scheduled Gate-Out Time at the origin airport. Flights may depart outside reportable hours, but must arrive during them. The reportable hours vary by airport and the results are reported by fiscal year (FY).	143.0	142.5	141.1	139.3	140.9	143.0	148.1	156.0
Taxi-In Time <i>Minutes per Flight</i> During reportable hours, the yearly average of the difference between Wheels-On Time and Gate-In Time for flights arriving at the selected airport from any of the Aviation System Performance Metrics (ASPM) airports. Flights may depart outside reportable hours, but must arrive during them. The reportable hours vary by airport.	10.1	9.9	9.0	9.2	9.9	10.8	12.0	11.8
Taxi-Out Time <i>Minutes per Flight</i> During reportable hours, the yearly average of the difference between Gate-Out Time and Wheels-Off Time	15.8	15.5	14.6	14.6	14.8	15.4	16.0	17.6

for flights from the selected airport to any of the ASPM airports. Flights must depart during reportable hours, but may arrive outside them. The reportable hours vary by airport.	13.8	13.3	14.0	14.0	14.6	13.4	10.7	17.0
--	------	------	------	------	------	------	------	------

1 Consistent data for the time period prior to FY 2011 are not available.

As described by the International Civil Aviation Organization (ICAO), *efficiency addresses the operational and economic cost-effectiveness of gate-to-gate flight operations from a single-flight perspective. In all phases of flight, airspace users want to depart and arrive at the times they select and fly the trajectory they determine to be optimum.*

Capacity Performance Indicator

Performance Indicator (FY)	2009	2010	2011	2012	2013	2014	2015	2016
Average Daily Capacity <i>Number of Operations</i> During reportable hours, the average daily sum of the Airport Departure Rate (ADR) and Airport Arrival Rate (AAR) reported by fiscal year (FY). The reportable hours vary by airport.	2,921	2,846	2,938	2,976	2,938	2,746	2,814	2,881
Average Hourly Capacity During Instrument Meteorological Conditions (IMC) <i>Number of Operations</i> The average hourly capacity reported during IMC weather conditions (as defined by ASPM). Capacity is defined as the sum of Airport Departure Rate (ADR) and Airport Arrival Rate (AAR). It is calculated based on the reportable hours at the destination airport. The reportable hours vary by airport.	175	172	174	178	176	166	175	178

As described by the International Civil Aviation Organization (ICAO): *The global Air Traffic Management (ATM) system should exploit the inherent capacity to meet airspace user demands at peak times and locations while minimizing restrictions on traffic flow. ICAO also notes: The ATM system must be resilient to service disruption and the resulting temporary loss of capacity.*

Additional Links

[NextGen Implementation Plan](#)

[View City Pairs Data](#)